

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
31 July 2003 (31.07.2003)


PCT

(10) International Publication Number  
**WO 03/062740 A1**

- (51) International Patent Classification<sup>7</sup>: **G01B 5/00**
- (21) International Application Number: **PCT/GB03/00251**
- (22) International Filing Date: **22 January 2003 (22.01.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
**0201362.1** **22 January 2002 (22.01.2002)** **GB**
- (71) Applicant (for all designated States except US): **RENISHAW PLC.** [GB/GB]; New Mills, Wotton-under-Edge, Gloucestershire GL12 8JR (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **McMURTRY, David,** [GB/GB]; Park Farm, Stancombe, Dursley, Gloucestershire GL11 6AT (GB).
- (74) Agent: **FOWLER, Maria, Jayne;** Renishaw plc, Patent Department, New Mills, Wotton-under-Edge, Gloucestershire GL12 8JR (GB).
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).**

[Continued on next page]

(54) Title: **RE-ORIENTATABLE SAMPLE HOLDER**



(57) Abstract: A device is disclosed having a base (2), and a re-orientable sample holder (4) adapted on at least first and second sides to be repeatably (perhaps kinematically) mounted to the base (2) wherein the relationship between the at least two surfaces when mounted on the base is known whereby when a sample (13) is mounted to the holder, the relationship between the different orientations of the sample when different surfaces of the holder are received on the base is known. The relationship between the at least two surfaces may be established by reference features on the sample holder (4) which provide positional information about the holder when received on a base. The reference features may be provided by a reference block, spheres or rods associated with the holder. Also disclosed is a device for and methods of operating on, for example scanning or machining, a sample in at least two stages using a base and re-orientable sample holder according to the invention.

WO 03/062740 A1

**Declaration under Rule 4.17:**

- of inventorship (Rule 4.17(iv)) for US only

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

## RE-ORIENTATABLE SAMPLE HOLDER

This invention relates to a reorientable sample holder whose location and orientation can be determined. For example, it may be used for the scanning of samples in two stages and matching together the data from the two stages providing coherent information. A preferred form relates to the scanning of dentalware such as frameworks for dentures.

10

One way that three-dimensional samples are scanned involves a stationary sample, a probe having three dimensional movement and styli that can access the whole surface of the sample including the underside enabling the whole surface to be scanned.

15

A problem with this method is that the equipment used requires a relatively large working space so it is unsuitable for situations where there are size limitations. A solution to this problem is to rotate the sample during the scanning process as this reduces the number of degrees of freedom that the probe requires. However, this solution results in further problems when scanning samples which have undercuts as this can lead to incomplete scans. Different problems are encountered when elongate samples, such as dental bridges, are involved.

25

The present invention provides a device comprising:

30

a base; and

a re-orientatable sample holder adapted on at least first and second sides to be repeatably mounted on the base characterised in that the relationship between the at least two surfaces when mounted on the

base is known whereby when a sample is mounted to the re-orientatable sample holder, the relationship between the different orientations of the sample when different surfaces of the re-orientatable sample holder are  
5 received on the base is known.

The surfaces of the re-orientatable sample holder which are adapted to be repeatably mounted on the base have a unique relationship to each other which can be  
10 mathematically defined. Thus, the sample holder can be re-orientated without losing the location of a first surface with respect to the base, and a sample located thereon. One way to mathematically define this relationship is by using reference features.

15 The relationship between the at least two surfaces of the re-orientatable sample holder is established by a plurality of reference features on the re-orientatable sample holder which provide positional information  
20 about the re-orientatable sample holder when received on a base. Positional information includes one or more of translational and rotational information.

Reference features may be provided by one of a number  
25 of methods including the provision of a reference block of material of known dimensions and having machined faces which adjoins or forms part of the re-orientatable sample holder. Alternatively three spheres or rods may be provided which protrude from the re-orientatable sample holder and are accessible  
30 regardless of which surface of the re-orientatable sample holder is received on the base. Other references may be taken from the sample holder itself.

In a preferred embodiment, the reference features are provided by surfaces which are commensurately larger than a device used to locate the surfaces in space (a probe or laser spot, for example) whereas the sample holder must be of sufficient size to hold and/or support a sample. If the reference features are on such a block of material, machining costs are reduced. This is because the sample holder does not have to be machined to the same degree of precision as it would have been to provide the reference features.

In a preferred embodiment, the re-orientatable sample holder is kinematically or quasi-kinematically received on the base by a kinematic mount. This ensures that when the sample holder is re-orientated, the position of an attached sample with respect to the new orientation will either be known (if the reference features have been datumed for that sample holder on that base previously) or can be determined using the reference features.

According to a second aspect of the present invention, there is provided a device enabling operation on a sample in at least two stages comprising:

25 a base;

a re-orientatable sample holder adapted on at least first and second sides to be repeatably mounted on the base; and

30 an operating system for operating on the sample when the at least first and second sides of the re-orientatable sample holder are repeatably mounted on the base;

characterised in that the relationship between the at least first and second sides of the re-orientatable

sample holder when mounted on the base is known enabling the at least two stages of an operation to be joined or matched.

- 5 Preferably, the relationship between the at least first and second sides of the re-orientatable sample holder is established by a plurality of reference features on the re-orientatable sample holder which provide positional information about the re-orientatable sample  
10 holder when received on the base.

According to a third aspect of the present invention there is provided a method of operating on a sample in at least two stages comprising:

- 15 providing a base;  
locating a re-orientatable sample holder on the base the re-orientatable sample holder being adapted on at least first and second sides to co-operate with the base;  
20 providing a plurality of reference features capable of supplying data about the position of the re-orientatable sample holder; and  
furnishing an operating system;  
wherein a first operation is made by the operating  
25 system when the first side of the re-orientatable sample holder co-operates with the base and a second operation is made when the second side of the re-orientatable sample holder co-operates with the base and the at least two operations are matched together  
30 using the data provided by the reference features.

According to a fourth aspect of the present invention there is provided a method of operating on a sample in at least two stages comprising the steps of:

providing a base;  
providing a re-orientatable sample holder which is adapted to be received kinematically on the base on at least first and second sides wherein the relationship  
5 between the first and second sides is known;  
placing the re-orientatable sample holder on the base on its first side;  
operating on a first stage of a sample held in the sample holder;  
10 re-orientating the sample holder with respect to the base onto its second side; and  
operating on a second stage of a sample held in the sample holder; wherein the  
operations of the first and second stages of the  
15 sample are matched using the relationship between the first and second sides.

When a kinematic location is used, the reference features for a particular pair of holder and base do  
20 not need to be re-datumed or re-referenced for future operations.

An operation includes the performance of a practical work on a sample such as scanning a surface profile,  
25 machining the sample, inspecting it or measuring it in some other manner.

The invention will now be described by example with reference to the accompanying drawings, in which:

30 Fig 1 shows an isometric view of a scanning apparatus using a device according to the invention;

Fig 2 shows an isometric view of device according to the invention;

Fig 3 shows an isometric view of a further device

according to the invention;

Fig 4 shows an isometric view of an alternative device according to the invention;

5 Figs 5 a-g show schematically the manufacture of a dental coping using a device according to the invention;

Fig 6 shows isometrically an indexable device according to the invention; and

10 Figs 7a and b show plan views of re-orientatable sample holders according to the invention.

Figures 1 and 2 show a device 1 having a base 2 with a support surface 3. A re-orientatable sample holder 4 is T-shaped and has three ball bearings 5,6,7 embedded in  
15 both its upper surface and in its lower surface (not shown). One ball bearing is disposed near each end of the 'T' on each side. A cube 8 is adjoined to the re-orientatable sample holder 4 and has four machined faces 9,10,11,12 which provide reference features. A  
20 tooth framework 13 is secured to the sample holder 4 via removable end pieces 14, 15 which are secured by screws 16,17 to each end of the top of the 'T' of the sample holder.

25 The tooth framework 13 is attached to the sample holder by at least partially removing the screws 16, 17 that hold the end pieces 14,15 to the sample holder and inserting the ends of the framework 13. When the screws 16,17 of the end pieces 14,15 are tightened, the  
30 framework is held in position.

The reference features on cube 8 and the framework 13 are scanned by a contact probe 22. An alternative scanner would be a laser probe.



Referring now to Figure 2, the support surface 3 has a magnet 18 disposed at its centre and three v-shaped grooves 19,20,21 lying radially spaced 90° apart (thus forming a 'T' shape). The three ball bearings 5,6,7 in each side of the re-orientatable sample holder 4 are disposed so that one lies vertically above/below another thus, each set of three balls co-operates with the three v-shaped grooves 19,20,21 in the support surface 3. This means that when the sample holder is reversed with respect to the base, the sample holder and thus the sample held therein are located in substantially the same place.

It will be appreciated that the grooves 19,20,21 and balls 5,6,7 form a (slightly degenerate) kinematic mount. Kinematic mounts of various types are well known, and described in (for example) HJJ Braddick, "Mechanical Design of Laboratory Apparatus" Chapman and Hall, London, 1960. Other kinematic mounts (and quasi-kinematic or partly degenerate kinematic mounts) may be used instead.

In order to obtain a complete scan of the surface of the framework 13, the framework is secured to the sample holder 4 as described above. The sample holder 4 is then placed on the support surface 3 in an orientation such that each ball bearing 5,6,7 co-operates with a groove 19,20,21. The magnet 18 ensures that this position is maintained until the sample holder 4 is removed from the base 3. Assuming this is the first scan using this holder and base i.e. the relationship between the two surface is not known, then firstly reference features are pinpointed followed by a scan of the upper portion of the framework 13. Once

this first part of the scan is complete, the sample holder 4 is reversed with respect to the base 3. Reference features for this second surface are pinpointed or located this time however, the reference  
5 feature for the vertical position is taken from a different face of the reference block 8 as the sample holder 4 is now reversed compared with its original position. The lower portion of the framework 13 is now scanned.

10

As the sample holder is kinematically located on the base, the four reference surfaces 9,10,11,12 need only be referenced once in respect of that sample holder when used with that base. Thus, the above example  
15 would only apply on first use of that sample holder with that base. The reference information could then be stored either in writing or as a part of a scanning programme so a user need merely know which base and holder were being used to access the reference data (if  
20 available). For ease of matching the two scanned portions, the side of the sample holder on the base should also be identified.

In order to obtain both positional and rotational  
25 information about the sample holder, both the reference block and sample holder are datumed. The upper surface of the sample holder is datumed at least three times in order to define the plane of the surface and thus sample holder. The top surface 11 of the reference  
30 block provides positional information in the Z direction and side surfaces 9 and 10 about the X direction. An edge (either the top of the "T" or the parallel edge to this) of the sample holder is also datumed at two locations to establish the end location

of the holder. This information is required for each surface of the holder which can be received on the base. In order to match the data from the different part scans, the other dimension required is the depth  
5 of the reference block between the two surfaces. Note when there are more than two surfaces capable of being received, this dimension will be different for each pair of surfaces. The person skilled in the art will appreciate that there are alternative ways of obtaining  
10 the data needed to establish where the sample holder is in space.

One such alternative to providing reference features in order to match-up part scans (or other operations), is  
15 to use computer software and processing to re-orient and re-position the part scans in relation to each other and thus enable the production of a more complete scan.

20 The reference block 8 is accurately machined so that each face is perpendicular to the adjacent faces. The distance between each set of opposite faces of the block needs to be known or measured (preferably under the same conditions as the framework scan). The  
25 references taken for each part of the scan in conjunction with the distance between the opposite faces of the block can then be used to match the two stages or parts of the scan (using appropriate computer software) adjusting said scans to take in consideration  
30 differences in the height and rotation of each part scan resulting in a complete matched scan of the framework.

When only two parts of a scan are being matched, it is

less important to know which orientation is being scanned at one time as there are only two different ways that the data can be matched. When there are more scanning stages to be matched, it is advised that the orientation of the sample holder is also identified to avoid complications and possible errors when applying the reference data to the scanned data.

If computer software and processing is used to match-up part operations rather than reference features, then identification of the surface received on the base is useful in order that the programme can learn how the different part operations are likely to fit together, reducing processing time.

Fig 3 shows a further sample holder 30 where the sample 31 is secured to the sample holder 30 using two slots 32,33 through the thickness of the sample holder. The sample 31 is secured at each end by glue to a threaded cylinder 34. The cylinder 34 is secured with respect to the slot by two nuts 35, one located either side of the slot 32,33.

In this example, the kinematic locator is reversed. The sample holder has three "v" shaped grooves 35 and a matching base (not shown) would have three co-operating balls protruding therefrom. Also, in this example the ends of the holder adjacent to 32 and 33 could be datumed to establish the x-direction location of the sample holder when on a base.

Fig 4 shows an alternative device 40 which is a cube having a sample holder 41 on one face and kinematic locators 42 which are three balls radially disposed by

120°, on each of the other faces. A base 43 has co-operating kinematic locators 44, which are three v-shaped grooves radially disposed by 120°.

- 5 In this example, the reference features are provided by the sample holder 41 which has a central collet 45 into which a sample or sample mount (for example a tube) may be inserted. The faces of the sample holder 41 are accurately machined to produce reference surfaces 46.
- 10 By measuring the distance from each face having a kinematic locator 42 to a respective reference surface 46 and the relative positions and orientations of each reference surface, the relative orientation and position of a sample (not shown) held by the sample
- 15 holder 41 in each possible kinematic location 42 with respect to the base 43 is known or derivable. This enables an operation, for example scanning of a sample to be performed in a number of stages, perhaps required due to the shape of the sample, and the data obtained
- 20 from these different stages to be matched together to produce a complete (if required) scan by the manipulation of each scanned data set using the measured information.
- 25 If a replica of the scanned sample is required, a machining process could be carried out using the same sample holder and base enabling the machining to either replicate the different scanning steps or, if more appropriate, to follow a route developed from the
- 30 scanned data which provides the most efficient or least complicated process. A device according to the invention could also be used for the inspection of samples.

Although the device has been described as a cube, it will be appreciated that any number of faces (two or more) may be utilised depending on, amongst other things, size of sample, shape of sample, complexity and  
5 available working space.

Figs 5a-g show schematically the manufacture of a dental coping. The re-orientatable holder 50 is cylindrical in shape and has a kinematic locator 51  
10 comprising three ball bearings radially spaced 120° apart on each rim 52a,b. A base 53 has a co-operating kinematic locator 54, three v-shaped grooves radially spaced 120° apart and describing a circle of the same diameter as the three ball bearings (Fig 5a).

15 The re-orientatable holder 50 may thus be positioned on the base 53 in two positions, one the reverse of the other. For clarity, reference features have not been shown in this drawing.

20 During the manufacture of a coping, both the internal and external surfaces of a blank must be machined. The external surface is produced as a replica of the original tooth shape and the internal surface is  
25 produced to fit onto an abutment which locates the tooth within a mouth. An ability to reverse the position of the coping during the manufacture is therefore advantageous.

30 The blank 55 is held in position on the re-orientatable holder 50 by a disc 56 which is in two parts and has a central hole (formed from a semi-circular hole in each part). The two parts of the disc 55 are attached by screws which allow a variability in the size of a blank

54 to be accommodated. Alternatively the disc 56 may be one piece, which has a slot and central hole to accommodate the blank, the disc being clamped by a screw.

5

The blank 55 is positioned with respect to the disc such that one end 57 of the blank is approximately level with the disc (Fig 5b).

10 The disc 56 is clamped to the re-orientatable device 50 by screws. Alternatively, the disc 56 is integrally formed as part of the re-orientatable holder which has a slot and is ring clamped to secure the blank centrally therein.

15

Once the disc 56 and blank 55 are securely positioned in the re-orientatable device, an internal bore 58 is produced by machining the end 57 of the blank which is almost level with the disc 56 (Fig 5c).

20

In order to provide stability to the blank for the second machining process, the internal bore 58 and a region 59 defined by the re-orientatable device is temporarily filled with a resin 60 (Fig 5d). Once the resin has cured sufficiently to provide strength and rigidity to the blank 55, the re-orientatable device 50 is reversed (Fig 5e), so the end 61 of the blank which stands proud of the disc is available for machining.

30 The outer surface of the end 61 of the blank is machined to produce the final shape of the coping 62 (Fig 5f). The resin is burned away leaving the coping 63 (Fig 5g). If the blank 55 is made from a ceramic material, then the burn-off could be incorporated as

part of the sintering process that occurs after machining.

The material used to support the partially machined  
5 blank need not be a resin but must be a removable material which provides sufficient support for the blank for example a wax or low melting point alloy.

Fig 6 shows an indexable device 70 comprising a  
10 circular base portion 73 with a plurality of ball bearings 74 disposed circumferentially around it. In between each ball bearing is a gap 76 which is approximately v-shaped. At the centre of the base portion 73, is a magnet 77 used to urge the re-  
15 orientatable device into position. A re-orientatable device 71 is a cube having on at least two faces 72a,b three radially spaced apart ball bearings 76 which describe a circle having substantially the same diameter as the plurality of ball bearings 74 in the  
20 base 73. The three radially spaced ball bearings 76 are spaced 120° apart and adapted to sit in the v-shaped gaps 75 formed between the plurality of ball bearings 74. This provides a number of different orientations in which the re-orientatable device may be  
25 located.

Alternatively, three v-shaped grooves may be provided thus, the re-orientatable device sits on the ball bearings rather than within the grooves therebetween.  
30 In both cases, a force is required to move the re-orientatable device out of its current position.

If the plurality of ball bearings 74 are accurately positioned, then the re-orientatable device 71 can be



indexed between different pairs of ball bearings enabling precise angular movement of say 7.5 or 15° intervals. This would enable small rotations of a sample held in a sample holder (not shown) on a face  
5 without the kinematic locators.

In addition to angular re-orientation, the re-orientatable device 71 may be relocated onto a different face 72b which may again be angularly  
10 re-orientated enabling a great number of orientations to be achieved.

Figs 7a and 7b show alternative embodiments of the invention where the repeatable locator itself is used  
15 to provide the initial reference or datum features used to relate two sides of a re-orientatable sample holder together.

The re-orientatable sample holder of Fig 7a, 80 is  
20 approximately triangular in shape having a ball bearing 81 disposed at each apex. A framework 82 is mounted or attached to one of the sides 83 of the sample holder. The three ball bearings 81 have a diameter which is larger than the thickness of the approximately  
25 triangular-shaped central portion of the sample holder. Thus, both sides of the sample holder may be repeatably located (in this example kinematically located) with respect to a base (not shown) by the provision of three v-shaped grooves or pairs of balls to provide a seating  
30 for each respective ball bearing 81. Once each ball bearing 81 has been datumed from each side whilst received on a particular base, and with knowledge of the diameter of the ball bearings 81, the operation on one side of a sample held in the sample holder can be

related to an operation on the reverse side. The datuming of the three balls provides the planar information about the re-orientatable sample holder.

- 5 Fig 7b shows a rectangular re-orientatable sample holder 85 with three rods 86 protruding from three sides of the sample holder. The three rods lie in substantially the same plane. A sample holder 87 is attached to a fourth side and also lies in
- 10 approximately the same plane as the rods. A base (not shown) in this example requires a groove within which each rod can be seated which may be raised with respect to the base surface for example, as formed by two protruding balls. The base may additionally or
- 15 alternatively include a recess to accommodate the thickness of the sample holder which lies below the rod when seated on the base. Again, each rod must be datumed, when each side of the sample holder is seated on the base. This information along with the diameter
- 20 or thickness of the rod provides enough information to match two operations carried out on a sample with different sides of the sample holder seated on the base.

## CLAIMS

1. A device comprising:

a base; and

5 a re-orientatable sample holder adapted on at least first and second sides to be repeatably mounted on the base;

characterised in that the relationship between the at least two surfaces when mounted on the base is known  
10 whereby when a sample is mounted to the re-orientatable sample holder, the relationship between the different orientations of the sample when different surfaces of the re-orientatable sample holder are received on the base is known.

15

2. A device according to claim 1, wherein the relationship between the at least two surfaces of the re-orientatable sample holder is established by a plurality of reference features on the re-orientatable  
20 sample holder which provide positional information about the re-orientatable sample holder when received on a base.

3. A device according to claim 2, wherein the reference features are provided by a reference block of known dimensions and having machined faces which  
25 adjoins the re-orientatable sample holder.

4. A device according to claim 2, wherein the reference features are provided by three spheres or  
30 three rods which protrude from the re-orientatable sample holder and are accessible regardless of which surface of the re-orientatable sample holder is received on the base.

5. A device according to any preceding claim wherein the re-orientatable sample holder is kinematically received on the base by a repeatable mount.
- 5 6. A device according to any preceding claim wherein the re-orientatable sample holder is adapted to receive teeth frameworks.
7. A device enabling operation on a sample in at  
10 least two stages comprising:  
a base;  
a re-orientatable sample holder adapted on at least first and second sides to be repeatably mounted on the base; and  
15 an operating system for operating on the sample when the at least first and second sides of the re-orientatable sample holder are repeatably mounted on the base;  
characterised in that the relationship between the  
20 at least first and second sides of the re-orientatable sample holder when mounted on the base is known enabling the at least two stages of an operation to be matched.
- 25 8. A method of operating on a sample in at least two stages comprising:  
providing a base;  
locating a re-orientatable sample holder on the base the re-orientatable sample holder being adapted on  
30 at least first and second sides to co-operate with the base;  
providing a plurality of reference features capable of supplying data about the position of the re-orientatable sample holder; and

furnishing an operating system;

wherein a first operation is made by the operating system when the first side of the re-orientatable sample holder co-operates with the base and a second operation is made when the second side of the re-orientatable sample holder co-operates with the base and the at least two operations are matched together using the data provided by the reference features.

10 9. A method of operating on a sample in at least two stages comprising the steps of:

providing a base;

providing a re-orientatable sample holder which is adapted to be received kinematically on the base on at least first and second sides wherein the relationship between the first and second sides is known;

15 placing the re-orientatable sample holder on the base on its first side;

operating on a first stage of a sample held in the sample holder;

20 re-orientating the sample holder with respect to the base onto its second side;

operating on a second stage of a sample held in the sample holder;

25 wherein the operations of the first and second stages of the sample are matched using the relationship between the first and second sides.

1/5





Figure 1

2/5.



3/5




Figure 3




Figure 4



4/5




Figure 6




Figure 7a




Figure 7b

5/5

Figure 5a




Figure 5b




Figure 5c




Figure 5d




Figure 5e




Figure 5f





Figure 5g



## INTERNATIONAL SEARCH REPORT

Intern Application No  
PCT/Gb 03/00251A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 G01B5/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 G01B A61C B23Q B01L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 1 142 541 A (RENISHAW PLC) 10 October 2001 (2001-10-10)	1,2,4-8
A	the whole document	3,9
Y	DE 198 27 788 A (BALLY GERT VON ;DIRKSEN DIETER (DE); BOLLMANN FRIEDHELM (DE)) 30 December 1999 (1999-12-30) abstract; figures 1,2 column 1, line 61 -column 3, line 6	1,2,4-8
A	EP 1 088 620 A (ADVANCE KK) 4 April 2001 (2001-04-04) abstract; figures 11,12 column 16, line 45 -column 17, line 17	1,7-9
A	US 4 478 580 A (BARRUT LUC P) 23 October 1984 (1984-10-23) abstract	1,7-9

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

21 May 2003

Date of mailing of the international search report

27/05/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax (+31-70) 340-3016

Authorized officer

Bockstahl, F

## INTERNATIONAL SEARCH REPORT

Intern<sup>l</sup> pplication No  
PCT/GB 03/00251

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,A	WO 02 28309 A (SJOELIN ROGER ;DECIM AB (SE)) 11 April 2002 (2002-04-11) abstract; figures 4,5 page 7, line 13 -page 8, line 31 -----	1,7-9
A	FR 2 278 034 A (THOMSON CSF) 6 February 1976 (1976-02-06) page 2, line 7 -page 4, line 32; figures 1-6 -----	1,7-9
A	DE 40 12 327 A (SCHREIBER HANS) 24 October 1991 (1991-10-24) abstract; figure 1 -----	1,7-9

## INTERNATIONAL SEARCH REPORT

Intern Application No

PCT, WO 03/00251

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1142541	A	10-10-2001	EP 1142541 A2	10-10-2001
			JP 2002011024 A	15-01-2002
			US 2001029010 A1	11-10-2001
DE 19827788	A	30-12-1999	DE 19827788 A1	30-12-1999
EP 1088620	A	04-04-2001	JP 11333667 A	07-12-1999
			JP 2000166943 A	20-06-2000
			JP 2000287997 A	17-10-2000
			AU 3954899 A	13-12-1999
			EP 1088620 A1	04-04-2001
			CN 1310656 T	29-08-2001
			WO 9961202 A1	02-12-1999
US 4478580	A	23-10-1984	DE 3203937 A1	01-09-1983
			EP 0086167 A2	17-08-1983
WO 0228309	A	11-04-2002	SE 518837 C2	26-11-2002
			AU 9041301 A	15-04-2002
			SE 0003575 A	05-04-2002
			WO 0228309 A1	11-04-2002
FR 2278034	A	06-02-1976	FR 2278034 A1	06-02-1976
DE 4012327	A	24-10-1991	DE 4012327 A1	24-10-1991
			DE 4013828 A1	09-01-1992

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

☐ BLACK BORDERS

☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES

☐ FADED TEXT OR DRAWING

☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING

☐ SKEWED/SLANTED IMAGES

☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS

☐ GRAY SCALE DOCUMENTS

☒ LINES OR MARKS ON ORIGINAL DOCUMENT

☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**